

Digital 2-channel receiver including 2 wireless outdoor cameras

Art. no. TVAC15300

Page 1 of 1



- Wireless receiver including 2 IR wireless outdoor cameras
- 2.4 GHz encrypted digital wireless transmission
- Transmission frame rate of 7 fps @ VGA resolution
- Digital wireless transmission of up to 2 cameras to recorders and monitors

With this complete set, comprising a digital 2.4 GHz 2-channel receiver and the 2 IR wireless external cameras, you can easily transmit video signals wirelessly to recorders or monitors over medium to long distances. Wireless signal transmission is an advantage everywhere where cables cannot be laid: both cameras transmit the video signal wirelessly to the receiver module. Faults and interference can be fully avoided due to the conversion into digital signals. The set contains everything necessary for a small wireless video system with up to 2 cameras – add a monitor or recorder, and you have video surveillance!

Technical Data:

Dimensions	163 x 89 x 25 mm
Resolution	640 x 480
Output	2x 3.5 mm Klinke (Video)
Width	163 mm
Height	89 mm
Camera inputs	2
Length	25 mm
Max. operating temperature	50 °C

Min. operating temperature	-10 °C
Net weight	0.27 kg
Transmission power	16 dBm
Sensitivity	-75 dBm
DC voltage supply	12 V
Power consumption	300 mA
Video signal	1.0 V p-p, 75 Ohm