



### Product description

Electric strike for horizontal panic door locks. Including surface-mounted housing  
ATP-----20105-01

### Overview of Advantages

- Vertical and horizontal mounting possible
- Due to 180° fitting, can be used DIN right and left

### Scope of delivery

- 1 piece electric strike

### Technical data

Dimensions	Height: 90 mm , Width: 20 mm , Depth: 28 mm
Version	Rim type strike
Latch version	other
Mounting	asymmetrical
Installation position	vertical
Configuration	Frame component
With fixing	No
With mechanical unlocking	No
With feedback signal	No
Opening direction according to DIN	left/right
Waterproof	No
Mounting method	applied
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
How they work	Fail-locked
Compatible with Amazon Alexa	No
IFTTT support available	No
Pulse contact	Yes
Adjustable keeper	No
Adjustable electric strike	No
Unlocking type	Standard version
Mechanical unlocking	No
Suitable for smoke protection door	No
Forend shape	other
With strike plate	Yes
Strike plate shape	other
Strike plate material	other
Base colour of the strike plate	black
Strike plate length	132 mm
Strike plate width	38 mm
Dead bolt cutout	No
Pre-equipped for bolt switch contact	No
Load cycles for in-plant test	250000
Changeable connection	No
Protective diode	No
Noise reduction	No
Drill hole offset by 1 mm	No
Unlocking time	0.8 s
Width of the strike plate (angle;lap)	45 mm
Operating temperature range	-15-40
Suitable for fire door	No

### Variants that can be ordered

Order number	Description
14.400-20105D11	With rim type housing, 6-12 V AC/DC
14.400-20105R11	With rim type housing, 8-16 V AC/DC
14.400-20105F11	With rim type housing, 24 V AC/DC
14.400-20105E31	With rim type housing, 12 V DC eE
14.400-20105F31	With rim type housing, 24 V DC eE